

LUXA 103 S360-100-12DE-UPWH



?? ???? : 1030052 ????? ???? ???? ???? ? ? ???? ???? ???? : 360 ???? ???? ???? : 2.5 - 3.5 ???? 5-1000 lx : ????? ???? ???? ???? ????
?? ???? ???? : 15 ???? ???? 30 ???? V AC 230 : ???? ???? IP 54 : ???? ???? ?

???? ???? : ???? ???? ???? ????
????

[?? ???? ???? ???? ???? ???? ?](#)

???

Function description

- Passive infrared presence detector, ceiling installation as supplied or flush-mounting by means of removable springs/protection cap and enclosed mounting frame
- 1 channel light (relay 230 V)
 - Circular detection area 360°, Ø 12 m (113 m²)
- at 3 m mounting height
- Extension of the detection area by parallel switching, a maximum of 8 detectors can be connected in parallel
-

- Networking with wall detector theMura Slave possible •
- Connection option for push-button for manual switching •
- Operation as fully or semi-automatic possible •
- One directional brightness measurement (mixed light measurement) •
- Teach-in function, pulse function, test function, staircase lighting function •
- Ready for operation immediately due to factory presetting •

?????? ??

???? ???? ???? ??? ????? ???? ?????.

// //