

PlanoSpot 360 DALI-2 S DE WH



?? ???? : 2030190 ????? ???? ???? ???? ???? ???? ???? ???? DALI-2 ????? ???? : 360 ???? ?????? ???? : 2- 3??? 10-10000 lx : ?????? ?????
???????? IP 20: ???? ?????

???? ???? : ???? ???? ???? ????
????

[?? ???? ?????? ??? ?????? ??????](#)

???

Function description

- Passive infra-red presence sensor for ceiling installation in false ceilings, DALI-2 certified
- Square detection area 360°, 7 x 7 m, (49 m²)
- at mounting height 3 m
- This device provides information about presence and brightness in the form of a DALI telegram in line with IEC 62386 Part 303/304
- 2 instances for presence - detection zone standard/reduced
- Optics can be tilted to adjust the detection area
- 3 mixed light measurements

- 4 instances for brightness - interior/centre/window/integral
- Easy to calibrate brightness measurement
- Test mode for checking function and detection area
- Configurable detection sensitivity

- Can be configured via DALI bus or remote control
- The «theSenda S» or «theSenda B» user remote controls can be used to dim or switch the lamps, to control the blinds, or to execute additional functions via the higher-level control
- Flat design with interchangeable bezel frame in different colours

?????? ??

???? ???? ???? ??? ????? ???? ?????.

// //